



Heidelberg Wallbox Home Eco Europe



Heidelberg Druckmaschinen AG Electric mobility division

Gutenbergring
69168 Wiesloch
Germany
Phone +49 6222 82-2266
E-mail: wallbox@heidelberg.com
Mannheim Registry Court
HRB 330004
wallbox.heidelberg.com

Publishing information

Publishing 06/21
Photos: Heidelberg Druckmaschinen AG
Fonts: Heidelberg Antiqua MI and Heidelberg Gothic MI

Technical highlights of the Heidelberg Wallbox Home Eco

- Connection to 230 volts or 400 volts
- Plug-and-play solution – easy installation by electrician or installation service
- 1-, 2- or 3-phase charging mode
- Integrated residual current detection: 6 mA DC
- Charging capacity (adjustable): e.g. 2.1 kW/3.7 kW/7.2 kW/11 kW
- Cable length: 3.5 m, 5 m, or 7.5 m

→ wallbox.heidelberg.com

Marks

Heidelberg and the Heidelberg logotype are registered trademarks of Heidelberg Druckmaschinen AG in the U.S. and other countries. All other trademarks are property of their respective owners.

Subject to technical modifications and other changes.



Do you have questions?
Simply use your smartphone to scan the QR code.
wallbox.heidelberg.com

Heidelberg Wallbox

Home Eco Europe

Technical data

Regulations	IEC 61851-1:2010
Charging performance, mode 3	up to 11 kW
Rated voltage	230 V – 400 V
Rated current	up to 16 A, adjustable from 6 A to 16 A in 2 A increments
Rated frequency	50 Hz
Charging mode	1-, 2- or 3-phase
Net types	TT/TN
Connection technology	Spring clamp technology
Cable inlet/cable entry	On-wall or in-wall, 9 to 17 mm
Connection cross-section	1 mm ² to 10 mm ² – Solid conductor (rigid) 1 mm ² to 10 mm ² – Fine-wire conductor (flexible) 1 mm ² to 6 mm ² – Fine-wire conductor with ferrule (flexible) The respective national installation regulations must be observed.
Charging connection/charging coupler	Type 2
Charging cable length	3.5 m, 5 m, or 7.5 m 3.5 m - 00.779.2794/04, 5 m - 00.779.2770/04, 7.5 m - 00.779.2879/02
Operation/status information	Pushbutton with LED
External release/locking of the Wallbox	Input for optional release switch
Safety class	IP54
Residual current detection	6 mA DC
Ventilation	No ventilation required
Protection against mechanical shock	IK08
Operating temperature range (°C)	-25 °C to +40 °C
Thermal behavior	The charging current is continuously provided within the operating temperature range. If the temperature is exceeded, the charging process is interrupted. The charging process is automatically restarted after a cooling phase.
Storage temperature range (°C)	-25 °C to +80 °C
Permissible relative humidity (%)	5 % to 95 %
Altitude (m)	Max. 3,000 meters above sea level
Protection class	I
Overvoltage category	III
Dimensions (W × H × D) (mm)	386 mm × 295 mm × 112 mm
Weight	approx. 8 kg