



Heidelberg Combox and Combox Lite.



**Heidelberger Druckmaschinen AG
Electric mobility division**

Gutenbergring
69168 Wiesloch
Germany
Phone +49 6222 82-2266
wallbox@heidelberg.com
wallbox.heidelberg.com

Publishing information

Publishing 04/21
Photos: Heidelberger Druckmaschinen AG
Fonts: Heidelberg Antiqua MI and Heidelberg
Gothic MI

Trademarks

Heidelberg, the Heidelberg logotype, Heidelberg
Combox, Heidelberg Combox Lite and Heidelberg
Wallbox Energy Control are registered trademarks
of Heidelberger Druckmaschinen AG in the U.S.
and other countries. All other trademarks are
property of their respective owners.

**Subject to technical modifications and other
changes.**

Smart control thanks to Heidelberg Combox

The Heidelberg Combox® provides smart, secure and user-friendly connectivity for up to 16 Heidelberg Energy Control® Wallboxes. It efficiently controls load management, and is therefore particularly suitable for employee and customer parking lots, apartment buildings, and hotel parking lots.

The easy-to-use software makes monitoring and analyzing charging stations and operations simple and intuitive, and you can also display the current charging status, view diagnostic data, and perform software updates.



Do you have questions?
Simply use your smartphone to
scan the QR code.
wallbox.heidelberg.com

Heidelberg Combox and Heidelberg Combox Lite. In detail.

Benefits for you


- Intelligent control of your charging infrastructure
- Simple and intuitive monitoring and analysis of your Heidelberg Energy Control Wallboxes
- Display of current charging status and diagnostic data
- Easy-to-use software
- Straightforward software updates for the entire charging infrastructure
- High-quality manufacture in accordance with the zero-defect principle
- Smooth connection to your backend (via OCCP 1.6)*
- Available in electrical stores and wholesale as well as from certified electricians



Heidelberg Combox

The **Heidelberg Combox** is intended for outdoor use. Its innovative design with status lighting and stainless steel casing corresponds to that of the Heidelberg Wallboxes.

The **Heidelberg Combox Lite**, on the other hand, is mounted directly on the sub-distribution board, or in the control cabinet.



Heidelberg Combox Lite

Technology and functionality are identical. Both versions have no charging functionality and can be installed physically independent of the Wallboxes.

Technical data

	Heidelberg Combox	Heidelberg Combox Lite
Rated voltage	230 V / 1 AC	230 V / 1 AC
Rated current	0.5 A	0.5 A
Rated frequency	50 Hz	50 Hz
Net types	TT/TN	TT/TN
Status information	2 LEDs on the front of the housing	2 LEDs on the front of the gateway module (status and power)
Safety class	IP54	Installation in housing (min. IP54)
Protection against mechanical shock	IK08	-
Operating temperature range (°C)	-25 to +40	-25 to +40
Permissible relative humidity (%)	20 to 90	20 to 90
Protection class	II	II
Overvoltage category	II	II
Dimensions (W × H × D) (mm)	295 × 386 × 112	200 × 65 × 130
Weight (kg)	Approx. 6.5	Approx. 0.4

* Requires a stable Internet connection